



PRODUCT DATA SHEET

CATEGORIES	
DATE	January 2012
PRODUCT NAME	Silktouch Thermo by Skivertex®
STANDARD WIDTH	54"
SELECTIONS	7 Items Lemu S1 7 Items Yana S2
ORDER QUANTITY	80 yards per item
SHEETS	Yes
THICKNESS	.007" Varies with depth of embossing
TYPICAL GSM	150
SURFACE	Polyurethane
BASE	Acrylic Latex Saturated Cellulose Blend
CUSTOMS DECLARATION	Paper; Impregnated with Latex
ORIGIN	USA
DECORATION BY	Burnishing (by Blind Stamping), Foil Stamping
GLUING	BACK: Animal, Synthetic, Hot Melt FACE: Synthetic
SPECIALS	2000 yards per item Limited Colors, Prints and Embossings
SPECIAL WIDTH	Yes; 25,000 yard minimum
RESTRICTIONS	Not available with Series 3 or Metallics
SPECIAL NOTICE	SLIGHT COLOR VARIATION SHOULD BE EXPECTED. HEAT AND PRESSURE COULD ACTIVATE COLOR CHANGE.
HEAT BURNISHING PROCESS	260°F - 280°F, 1 second dwell time, 80 PSI Make ready for evaluation on stamping equipment for exact conditions are critical
SAMPLE SERVICE	Sheets 26" x 20"

LOGISTICS/PACKAGING	
TYPE OF PACKAGING	Rolls in moisture barrier paper or on pallets, sheets on skids
CORE	3"
STANDARD ROLL LENGTH	250 yards
GROSS WEIGHT	117 pounds per standard roll

FiberMark
70 Front Street
West Springfield, MA 01089
USA

Customer Service Telephone: 800 843 1243
Customer Service Fax: 413 532 4810